



September 22, 2011

Subject: Bio-Fuel Compatibility

To Whom It May Concern:

DoubleTrac® by OmegaFlex® metallic piping system (pipe, fittings, and accessories) is fully listed to UL971A, Metallic Underground Piping for Flammable Liquids – Series DoubleTrac – 1, 1-1/2 and 2 in. diameter Flexible Type Piping for use as Integral Primary/Secondary Pipe System (PS), Normal Vent (NV) and Vapor Recovery (VR) for underground fuel transfer applications such as gas stations for Motor Vehicle (MV), High Blend (HB), Concentrated (CT) and Aviation and Marine (A&M) Fuels.

The DoubleTrac® piping system (pipe, brass and stainless steel fittings, and accessories) are compatible with all concentrations of ethanol and ethanol blended fuels, from 0% to 100% ethanol content in gasoline as well as all concentrations of methanol blended fuels.

Additionally the DoubleTrac® piping system (pipe, stainless steel fittings, and accessories) are compatible with all concentrations of bio-diesel.

For questions or other information, please contact Dean Rivest, contact information below.

Respectfully,

Dean W. Rivest, P.E.

Dean W. Rivest P.E.

Vice President & General Manager Industrial Division OmegaFlex Inc.

dean.rivest@omegaflex.net

ph: 610-524-7272 fax: 610-524-6484